TECHNICAL DATA SHEET

Ecosoft PINK-20 Wasserenthärter

No Installation Kit / None

INTEGRATED SOFTENERS

2-7 personen

Please choose:	**No Installation Kit**
Options:	**None**
Warranty	**Manufacturer's warranty**



TECHNICAL SPECIFICATIONS

TECHNICAL DATA

Softening Capacity (at 7.5°dH)	**9.35 m³**
Salt consumption per liter of Resin	**100 grams**
Salt consumption per regeneration	**2.0 kg**
Service flow rate	**1.8 m³/h**
Operating pressure	**2-6 bar**
Pressure loss at max. flow	**0.5 bar**
Max. water temperature	**30 °C**

EXTRA

Series	**Pink**
Number of people	**3 persons**

CONTROL VALVE

Water connection type	**3/4" OD straight**
Drain connection type	**½ OD or 12 mm**
Power connection type	**230/ 50/24 V**
Power consumption	**30 watts**
Control valve	**Clack® WS1DV**
Regeneration duration	**75 minutes**

MEASUREMENTS

Resin Lifespan	**30 years**
Resin Volume	**20 L**
Salt tank capacity	**25 kg**
Length	**43 cm**
Width	**27 cm**
Height	**74 cm**
System weight	**27.5 kg**