TECHNICAL DATA SHEET

# Ecosoft PINK-20 Adoucisseur d'eau

No Installation Kit / None

INTEGRATED SOFTENERS

2-7 personen

| | |
|---|---|
| Please choose: | **No Installation Kit** |
| Options: | **None** |
| Warranty | **Manufacturer's warranty** |



## TECHNICAL SPECIFICATIONS

### TECHNICAL DATA

| | |
|---|---|
| Softening Capacity (at 7.5°dH) | **9.35 m³** |
| Salt consumption per liter of Resin | **100 grams** |
| Salt consumption per regeneration | **2.0 kg** |
| Service flow rate | **1.8 m³/h** |
| Operating pressure | **2-6 bar** |
| Pressure loss at max. flow | **0.5 bar** |
| Max. water temperature | **30 °C** |

### EXTRA

| | |
|---|---|
| Series | **Pink** |
| Number of people | **3 persons** |

### CONTROL VALVE

| | |
|---|---|
| Water connection type | **3/4" OD straight** |
| Drain connection type | **½ OD or 12 mm** |
| Power connection type | **230/ 50/24 V** |
| Power consumption | **30 watts** |
| Control valve | **Clack® WS1DV** |
| Regeneration duration | **75 minutes** |

### MEASUREMENTS

| | |
|---|---|
| Resin Lifespan | **30 years** |
| Resin Volume | **20 L** |
| Salt tank capacity | **25 kg** |
| Length | **43 cm** |
| Width | **27 cm** |
| Height | **74 cm** |
| System weight | **27.5 kg** |