TECHNICAL DATA SHEET

# Aqmos R2D2-32 Waterontharder

No Installation Kit / Met drukverhoger

INTEGRATED SOFTENERS

1-3 personen

| | |
|---|---|
| Article number | **test1** |
| Please choose: | **No Installation Kit** |
| Accessoires ofzo | **Met drukverhoger** |
| Warranty | **5 + 5 year warranty** |



| FOR | CAPACITY | FOOTPRINT | SALT REFILL |
|---|---|---|---|
| **1-3** persons | **3,200** L at 7.5 °dH | **22 x 46** cm | **3-5** months |

## TECHNICAL SPECIFICATIONS

### TECHNICAL DATA

| | |
|---|---|
| Softening Capacity (at 7.5°dH) | **3,200 L** |
| Salt consumption per liter of Resin | **160-200 grams** |
| Salt consumption per regeneration | **1.6 kg** |
| Service flow rate | **1,0 m³/h** |
| Operating pressure | **2-6 bar** |
| Pressure loss at max. flow | **0,6 bar** |
| Max. water temperature | **30 °C** |

### EXTRA

| | |
|---|---|
| Series | **R2D2** |
| Number of people | **1 person** |

### CONTROL VALVE

| | |
|---|---|
| Water connection type | **3/4" OD 90° elbow** |
| Drain connection type | **12 mm** |
| Power connection type | **230/ 50/24 V** |
| Power consumption | **3 watts** |
| Control valve | **BNT1650** |
| Regeneration duration | **75 minutes** |

### MEASUREMENTS

| | |
|---|---|
| Resin Lifespan | **30 years** |
| Resin Volume | **8 L** |
| Salt tank capacity | **25 kg** |
| Length | **46 cm** |
| Width | **22 cm** |
| Height | **65 cm** |
| System weight | **17 kg** |

## WHAT'S INCLUDED

| | |
|---|---|
| **1 x** | AQMOS R2D2-32 water softener |
| **2 x** | BSPT connector 3/4" 90° |
| **1 x** | 12 V power adapter |
| **1 x** | Manual |
| **1 x** | Pressure booster 1.2 bar |
| **1 x** | Wall bracket for pressure booster |

## DIMENSIONS

